

MODEL Magnum 4+2G



THIS CART IS SUITABLE FOR:

Community Transporter, Commercial Service, Industrial Facilities

The Trusted ECAR Golf Australian Warranty

PERSONAL USE WARRANTY

- 7 years on Chassis
- 5 years unlimited kilometre warranty on Lithium Battery
- 3 years on Lithium Battery Charger
- 3 years on Electrical & Mechanical

ECAR OEM Lithium Battery Options

PRO·Li Core 105Ah

Designed and produced by ECAR Golf. This certified and integrated battery system is designed for approximately 4-6 hours of use per charge.

PRO·Li Plus⁺ 150Ah

Designed and produced by ECAR Golf. This certified and integrated battery system is designed for approximately 6-10 hours of demanding use per charge and improved battery performance.

ECAR PRO-LI Lithium Battery systems are compliant with AS/NZS 3001.2:20022 for use in Australia and are an OEM battery, not a third party system. We are fully insured and fully certified.

COMMERCIAL USE WARRANTY

7 years on Chassis

5 years unlimited kilometre warranty on Lithium Battery 3 years on Lithium Battery Charger 2 years on Electrical & Mechanical

Standard Colour Options



This cart is not for public road use - compliant for conditional or limitedaccess registration only. Please consult your local dealer or state/territory transport department for more information on the approve use.

ecar Magnum 4+2G

TECHNICAL DATA & SPECIFICATIONS

Cart Main Electrical Components	Proprietary Controller	ECAR 350A AC Controller. 48V 350A System (Programmable).
	Electric Motor	LT AC Synchronous (Induction) 48V/4kW (Higher Torque, Brushless).
	Batteries (Australia/NZ Models)	Certified OEM ECAR PRO-Li Lithium Core 105Ah and Plus+150Ah Systems.
	Batteries (SE Asia, UAE Models)	ECAR No Maintenance Gel, 8V-150Ah x 6. (Certified & Manufacturer Approved ECAR PRO-Li Lithium options available)
	Charger (Australia/NZ Models)	ECAR OEM PRO-Li On board Intelligent Lithium Battery Charger. RCM Approved & Compliant for use with only ECAR OEM PRO-Li Batteries.
	Charger (SE Asia, UAE Models)	On board Intelligent Delta Q 48V DC Output Charger. 6-8hr Charge time from SOC >15%
	DC-DC Converter	Isolated DC-DC Converter 48V/12V Output 300W Output
Steering & Mechanical	Steering System	Two-way rack & pinion steering system, automatic gap compensation function for direct & accurate control.
	Braking System	4 Wheel Hydraulic Disc Brakes with Automatic Electromagnetic Parking Brake.
	Front Suspension System	Dual Swing Arm with MacPherson Independent suspension on both front wheels; coil spring + cylinder hydraulic shock absorbers. (Enhanced Automotive style)
	Rear Suspension System & Trans-axle	Integrated rear Trans-axle. Ratio: 16:1 (LWB) with coil spring + cylinder hydraulic shock absorbers.
	Wheels & Tyres	12" Alloy Wheels with 23x10.5-12 off road Tyre.
Cart Exterior	Body	Injection moulded Automotive Painted Front Body Panels with UV resistant clearcoat. Poly rear body panel for additional styling.
	Roof	Automotive engineering PP material injection mould Roof with aluminium uprights
	Chassis	3 stage powder-coated RHS Type and electro-treated chassis (7 yr ECAR Only Chassis Warranty)
	Windshield	2 piece Acrylic Folding Windshield
Lighting	Lights and Warning signals	LED High/Low Beam Headlights, LED Daytime Running Lights, LED Indicators, LED Rear Tail Lights, LED Brake & Hazard Lights, Horn & Reversing Buzzer
	Additional Lighting Accessories	Consult an authorised dealer for 12V Lighting Accessories
Standard & Interior Features	Dashboard	50mm round instrument panel, digital vehicle odometer/speed meter showing speed & accurate Lithium Battery SOC (ECAR only) mounted on the steering column
	Interior Seating	Light Grey marine grade vinyl seats. Mid-back with folding armrests. Rear Seat with fixed armrests. Commercial rated. Rear Facing seat folds out seat to a flat platform.
	Interior floor	Alloy corrugated floor. Optional Rubber floor mat is available as an additional accessory (Consult authorised dealer)
	Rear-view Mirror	Interior Convex rear-view Mirror + L/RHS standard rear-view Mirrors.
Cart Main Dimensions	Length x Width x Height (mm)	3850(L)(including bull bar) x 1370 (W) x 2030mm (H)
	Tare Weight (No Batteries)	549kg
	Wheelbase overall length (center of front hub to center of rear hub)	2420mm
	Wheelbase width between (center of tread to center of tread)	Front 1024mm, Rear 1074mm
Cart Ratings	Rated Number of Passengers	(6) 4 Forward facing, 2 Facing Backwards
	Max. Recommended Driving Speed	25 km/hr (programmable 15-40km/hr). Legal Speed Limit 20km/hr
	Avg. Driving Distance per Charge	70-120 km (Battery Amp hour dependant) on flat ground per charge from 100% SOC)
	Maximum Recommended Grade	25% (20% for Hill Hold Limit)
	Load Ratings (kg) (level ground)	Towing: 350kg. Ball Vertical Weight: 50kg (rated on level ground). Rear Seat Platform: 150kg. Total Cart Load inc. Passengers & Cargo: 750kg
	Minimum Ground Clearance	Approximately 175mm
	Minimum Turning Radius	4.65m
	Rated Braking Distance	< 6m
	Avg. Energy Consumption per 100km	7.5-9.5kW/hr based on terrain and programmed parameters of the controller
Included HD Accessories	Standard (no additional charge)	Steel Powder-coated Commercial Bull bar, Rear Tow Bar, 3-point Seat Belts.

