MODEL

Magnum 4AT



THIS CART IS SUITABLE FOR:

Wheelchair Accessible Transport

The Trusted ECAR Golf Australian Warranty

PERSONAL USE WARRANTY

7 years on Chassis

5 years unlimited kilometre warranty on Lithium Battery

3 years on Lithium Battery Charger

3 years on Electrical & Mechanical

ECAR OEM Lithium Battery Options

PRO·Li Core 105Ah

Designed and produced by ECAR Golf. This certified and integrated OEM battery system is designed for approximately 2-3 rounds of golf per charge (course distance and cart load dependent).

PRO·Lí Plus⁺ 150Ah

Designed and produced by ECAR Golf. This certified and integrated OEM battery system is designed for approximately 3-4 rounds of golf per charge and improved battery performance.

ECAR PRO-Li Lithium Battery systems are compliant with AS/NZS 3001.2:20022 for use in Australia and are an OEM battery, not a third party system. We are fully insured and fully certified.

COMMERCIAL USE WARRANTY

7 years on Chassis

5 years unlimited kilometre warranty on Lithium Battery

3 years on Lithium Battery Charger

2 years on Electrical & Mechanical

Standard Colour Options



This cart is not for public road use - compliant for conditional or limitedaccess registration only. Please consult your local dealer or state/territor, transport department for more information on the approve use.



TECHNICAL DATA & SPECIFICATIONS

Cart Main Electrical Components	Proprietory Controller	ECAR 350A AC Controller. 48V 350A System (Programmable)
	Electric Motor	LT AC Synchronous (Induction) 48V/4kW (High Torque, Brushless)
	Batteries (SE Asia, UAE Models)	ECAR No Maintenance Gel, 8V-150Ah x 6. (Certified & Manufacturer Approved ECAR PRO-Li Lithium options available)
	Batteries (Australia/NZ Models)	Certified and Manufacturer Approved ECAR PRO-Li Lithium Core 105Ah or Plus+ 150Ah Systems.
	Charger (SE Asia, UAE Models)	On board Intelligent Delta Q 48V DC Output Charger. 6-8hr Charge time from SOC >15%
	Charger (Australia/NZ Models)	ECAR PRO-Li On board Intelligent Lithium Battery Charger. RCM Approved & Compliant for use with only ECAR PRO-Li Batteries.
	DC-DC Convertor	Isolated DC-DC Convertor 48V/12V Output 300W Output
Steering & Mechanical	Steering System	Two-way rack & pinion steering system, automatic gap compensation function for direct & accurate control.
	Braking System	4 Wheel Hydraulic Disc Brakes with Automatic Electromagnetic Parking Brake.
	Front Suspension System	Dual Swing Arm with MacPherson Independent suspension on all four wheels; coil spring + cylinder hydraulic shock absorbers. Automotive style
	Rear Suspension System & Transaxle	Integrated rear Trans-axle. Ratio: 16:1 (LWB) with coil spring + cylinder hydraulic shock absorbers.
	Wheels & Tyres	10" 'Bulldog' Alloy Rims with 205/65-10 High wall 4P Turf Tyre
Cart Exterior	Body	Injection moulded Automotive Painted Front Nose Cone with UV resistant clearcoat. Aluminium Sideskirt panels
	Roof	Automotive engineering PP material injection mould Roof with aluminium uprights
	Chassis	3 stage powder-coated RHS Type and electro-treated chassis (7 yr ECAR Only Chassis Warranty)
	Windshield	Acrylic 2-piece folding Windshield
Lighting	Lights and Warning signals	LED High/Low Beam Headlights, LED Daytime Running Lights, LED Indicators, LED Rear Tail Lights, LED Brake & Hazard Lights, Horn & Reversing Buzzer
	Additional Lighting Accessories	Consult an authorised dealer for 12V Lighting Accessories
Standard & Interior Features	Dashboard	50mm round instrument panel, digital vehicle odometer/speed meter showing speed & accurate Lithium Battery SOC (ECAR only) mounted on the steering column
	Interior Seating	Light Grey marine grade vinyl seats. Commercial rated.
	Interior floor	Alloy corrugated floor with 4 x secure tie-down wheelchair points
	Wheelchair Ramp & Fence	Aluminium Checkerplate with powdercoated Steel Frame folding Wheelchair Ramp - Fall Arrest Stainless Steel Fence on opposite side of wheelchaire zone for passenger protection. The ramp is lift assisted via a gas lift strut and secured in place with latches for safe travel
	Rear-view Mirror	Interior Convex rear-view Mirror + L/RHS standard rear-view Mirrors.
Cart Main Dimensions	Length x Width x Height (mm)	4352 (L) x 1210mm (W) x 1915mm (H)
	Tare Weight (No Batteries)	545kg
	Wheelbase overall length (center of front hub to center of rear hub)	3310mm Wheelbase widths: Front 895mm, Rear 1000mm
	Wheelchair Ramp (mm)	1370 (L) x 900mm (W) in loading position. 13 degree loading angle (on flat ground)
Cart Ratings	Rated Number of Passengers	(5) 1 x Driver, 3 x Passengers, 1 x Wheelchair forward facing
	Max. Recommended Driving Speed	25 km/hr (programmable 15-40km/hr). Legal Speed Limit 20km/hr
	Avg. Driving Distance per Charge	70-120 km (Battery Amp hour dependant) on flat ground per charge from 100% SOC)
	Maximum Recommended Grade	20% (15% for Hill Hold Limit)
	Load Ratings (kg)	Towing: 350kg (if fitted), Ball Vertical Weight: 50kg (rated on level ground) Total Cart: 800kg. Ramp rated to 250kg
	Minimum Ground Clearance	Approximately 120mm
	Minimum Turning Radius	5.8m
	Rated Braking Distance	< 6m 8.0-9.5kW/hr based on terrain and programmed params. of the controller
Included Magnum	Avg. Energy Consumption per 100km	
Accessories	Standard Included Accessory	Steel Powdercoated Commercial Bullbar, Tow Bar, Seat Belts
Optional Extras	5kW Motor Upgrade; Black or Beige Vinyl Seats, Marine Grade Rain Curtains (dealer installed locally)	